

## SUREBAND<sup>Clear</sup>

### Ideal for Acid / Caustic / E15 Oil and Diesel mist prevention

Manufactured from All-PTFE materials (no fibreglass) comprising clear ECTFE outer and multi-layered ETFE mesh inner. This material provides unparalleled chemical resistance. All our shields are tested on our hydrostatic pressure test facility, test certificates available on request.

The internal mesh is compressed against the flange and prevents direct and lateral spray. The liquid pressure inside is rapidly diffused, resulting in a safe drip-release.

SUREBAND<sup>Clear</sup> is very quick to install using heavy duty Velcro tabs which have been leak tested at various orifice sizes at pressure up to 75 Bar. It can be re-used in the event of a leak, thus providing a long term solution.

### Specification

Band Material:	ECTFE
Mesh Material:	ETFE
Fastener:	Heavy Duty Velcro
Shear force:	196 N
Max Temperature:	200 Deg C
Flange Ratings:	ANSI / DIN / many others
Pipe Sizes:	15mm to 1200mm
Leak Detection:	Visual Litmus Paper
Typical Applications:	Acid, Bases, Oil



This product can also be made to fit valves and other non-standard pipe joints, contact us for further information



**UK & Ireland, HQ**  
Flangeguards Ltd  
Unit 5, Cranes Close  
Basildon, Essex, UK, SS14 3JB  
☎ 01268 244369  
✉ sales@flangeguards.com